

GenLube 6681

Metal Lubricant



TYPICAL PROPERTIES

- Appearance: Clear amber liquid
- Specific Gravity: 0.870
- Flash Point: 140°F

SHIPPING

GenLube 6681 ships in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon plastic drums.

Description

The product formulation obtains the important balance of proper lubrication during metalworking, yet “vanishes” from parts in minimal time to avoid delays in the manufacturing process, and minimizing the need for manual cleaning of components. GenLube 6681 is non-corrosive and non-staining to aluminum, copper, steel, and their alloys.

Recommended Application

1

Product is used as received.

2

Can be applied by spraying, dipping, brushing, flooding, or roller coating methods.

Benefits

- Suitable for ferrous and non ferrous metals
- Suitable where surfaces are painted with oil paints
- Burns clean in annealing ovens
- Designed not to tarnish or attack metals
- Extra lubricity

Health & Safety

Gloves recommended when handling. Neoprene, nitrile, or PVC offers good protection.

Please refer to SDS for complete health and safety information.

Storage

Keep away from heat, sparks, or flame.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com