

# STRIPOXY 2800

Water Based Epoxy Paint Remover



## TYPICAL PROPERTIES

Appearance: Brown liquid  
Odor: Mild Odor  
pH: 3-4

## SHIPPING

Stripoxy 2800 is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

## Description

Stripoxy 2800 is used for paint removal of cured & uncured epoxy coatings from a variety of substrates ESPECIALLY DESIGNED FOR ALUMINUM AND NON FERROUS METALS. Stripoxy 2800 is also an adhesive remover, urethane paint stripper. Non-Flammable in nature. Low vapor pressure radically reduces VOC emissions. Ideal for soak tank application and also for spray application.

## Recommended Application

1

STRIPOXY 2800 is engineered for soak tank and spray applications.

It is diluted with water and used from 140 F to 170 F.

2

Rinse thoroughly.

By immersion or power washing.

## Benefits

Superior cleaning ability  
Low foaming  
Does not contain phenols, chlorinated or flammable solvents  
Water based product  
Works well on coated carbon steel, stainless steel and aluminum

## Health & Safety

Refer to SDS for complete health and safety information.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)