

STRIPOXY 2800

Water Based Epoxy Paint Remover



TYPICAL PROPERTIES

Appearance: Brown liquid
Odor: Mild Odor
pH: 3-4

SHIPPING

Stripoxy 2800 is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

Description

Stripoxy 2800 is used for paint removal of cured & uncured epoxy coatings from a variety of substrates **ESPECIALLY DESIGNED FOR ALUMINUM AND NON FERROUS METALS**. Stripoxy 2800 is also an adhesive remover, urethane paint stripper. Non-Flammable in nature. Low vapor pressure radically reduces VOC emissions. Ideal for soak tank application and also for spray application.

Recommended Application

1

STRIPOXY 2800 is engineered for soak tank and spray applications.

It is diluted with water and used from 140 F to 170 F.

2

Rinse thoroughly.

By immersion or power washing.

Benefits

Superior cleaning ability
Low foaming
Does not contain phenols, chlorinated or flammable solvents
Water based product
Works well on coated carbon steel, stainless steel and aluminum

Health & Safety

Refer to SDS for complete health and safety information.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com