

# CarpetGeneral Carpet Defoamer 5814

## TYPICAL PROPERTIES

- Appearance: off white liquid
- Odor: mild
- pH: 7.0-8.5

Foam suppressant

## Description

CarpetGeneral® Carpet Defoamer 5814 is a silicone emulsion that has excellent foam knockdown and suppression properties. It effectively controls foam caused by protein soils, soaps and detergents during carpet cleaning operations, especially hot water extraction. It is a non-hazardous, neutral, milky white liquid safe for use on a large variety of carpets. It is non-corrosive to equipment materials, including, polyethylene, polypropylene, PVC, FRP and stainless steel.

## Recommended Application

1

Do not apply directly to carpet.

2

### Wet Vacuums:

Pour Carpet Defoamer 5814 directly in vacuum tank at ratio of 1/2 oz. per gallon capacity or suction directly into vacuum hose.

3

### Carpet Extractors:

Carpet Defoamer 5814 can be applied directly to the extractor recovery tank walls using a hand sprayer or by pouring 1 to 2 ounces into the end of the extractor vacuum hose with the machine running.

## Benefits

- Concentrated formula for economical use
  - Non-hazardous
  - Excellent defoaming and foam suppressing properties
  - Non-corrosive to equipment
- = Neutral pH

## Health & Safety

Please refer to SDS for complete health and safety information.

## Note

Avoid spraying on hard or resilient floors as it may cause slipperiness.

## Application

If foam occurs during cleaning, spray Carpet Defoamer 5814 directly into foam in recovery tank as needed.

