



Graffitex 4800

Paint Stripper

Description

Graffitex 4800 is a water based, low VOC, gel paint stripper. Graffitex 4800 is a cost effective, environmentally friendly, thixotropic liquid gel paint remover of uncured and old cured paints and coatings. Specifically designed for graffiti removal. Safe for use on concrete, stainless steel, aluminum and other nonferrous alloys, wood, and masonry substrates.

Recommended Application

TYPICAL PROPERTIES

Color/Appearance: Clear thixotropic gel paint remover with orange emulsion
Odor: Mild sweet aroma
VOC: 0.528 Lbs. Per gal.(0.63 g/l)
Flash Point: in excess of 212 F (100 c)
Freezing Point: 32 F (0 c)
pH : 2-3 (Direct Reading)
Temperature use Range: If the temperature is below 40 F, Graffitex 4800 may work too slowly to be effective.

SHIPPING

Graffitex 4800 is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

1

Before beginning application, protect adjacent areas.

Although Graffitex 4800 is effective on glass, metal, wood, and stone, it may soften some resinous materials, so mask off any nearby caulking and rubber with plastic tape and plastic sheeting. Also protect nearby painted surfaces that you do not intend to strip. If you are uncertain whether Graffitex 4800 will harm a surface either test it first or simply cover the surface.

2

Stir to a uniform consistency

3

Apply a thick coat of Graffitex 4800 to the area being stripped using a paintbrush or a wallpaper paste brush for larger areas.

Depending on the type of coating being removed, the temperature, and the number of layers present, Graffitex 4800 may take several minutes, or several hours to strip the coating.

4

Test the finish.

This determines whether coatings are satisfactorily softened for removal.

5

Apply additional material if necessary.

If Graffitex 4800 is completely absorbed, yet doesn't completely soften all built-up layers of the coatings, apply a second coat of material and give it time to work. Repeat this procedure until all built-up layers are soft enough for easy removal.

6

Remove softened finish.

Once the finish is completely softened, scrape it off with a putty knife indoors and a pressure washer outdoors. If using pressure on wood, take care to prevent damaging the fibers.

7

Clean up any residue and remaining finish.

This is done on wood by lightly sanding and on other surfaces by agitating and soapy water.

Benefits

Water-based, gel type viscosity
Low VOC, no Methylene chloride
Removes high performance coatings such as two component epoxy and urethane

Health & Safety

Please refer to SDS for complete health and safety information.

Storage

Keep in sealed containers and store in a well ventilated area. Mix well and form the emulsion before use.

Coverage

Coverage is approximately 60-70 sq. feet per gallon

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com