

# LATEXSOL 6840

## LATEX PAINT REMOVER



### TYPICAL PROPERTIES

Appearance Form: Brown liquid  
Odor: Mild Odor  
pH: 3-4

### SHIPPING

LATEXSOL 6840 is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

### Description

Water based eco friendly Latex paint Remover For for IBC Totes and Tank Trailer cleaning. LATEXSOL 6840 is non-flammable in nature. Low vapor pressure radically reduces VOC emissions. Ideal for soak tank application and also for spray application.

### Recommended Application

- 1 LATEXSOL 6840 is engineered for soak tank and spray applications.
- 2 Dilute with 50% water. Use from 140°F to 185°F.

### Benefits

- Superior cleaning ability
- Low foaming
- Does not contain phenols, chlorinated or flammable solvents
- Water based product
- Works well on coated carbon steel, stainless steel and aluminum

### Health & Safety

Please refer to SDS for complete health and safety information.

### Storage

LATEXSOL 6840 has a shelf life of 1 year from date of manufacture.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)