

# Metal Cleaner 100

Urethane Remover

## TYPICAL PROPERTIES

- Appearance: Clear, light straw to amber liquid
- Odor: Mild
- Weight per Gallon: 8.5 - 8.7 lbs/gal
- Boiling Point: 396 °F

## Description

Metal Cleaner 100 is a non-chlorinated metal cleaner formulated with a blend of ingredients designed for the foundry industry to remove build up of urethane resins from metal toolings or core boxes. Metal Cleaner 100 should not be used on nonmetallic patterns, core boxes or tooling. Metal Cleaner 100 can also be used to remove urethane from metal tools and substrates.

## Recommended Application

1

Metal Cleaner 100 can be applied by spray or brush.

To provide optimum results it is recommended that the product be allowed to set for approximately three (3) to ten (10) minutes after application, depending on the severity and thickness of the urethane resin layer to be removed.

## Health & Safety

Avoid contact with skin and eyes; wash thoroughly after handling. Avoid breathing vapor; use with adequate ventilation. Refer to SDS for complete health and safety information.

## Storage

Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Keep this container and vapors from this container away from heat, sparks, flame, and other ignition sources

## Application

Due to the relatively slow evaporation rate, compared to methylene chloride based formulas, the additional step of air blow off may be necessary before resuming production with core boxes or tooling.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)