



TYPICAL PROPERTIES

- Water based
- Blue in color

SHIPPING

Ships in 1 Gallon Plastic Jug, 5 Gallon Plastic Bucket, 55 Gallon Open Head Plastic Drum

Model Mask 1186

Peelable Coating/Temporary Maskant

Description

Formulated for use in model making, Model Mask 1186 applies to a variety of substrates, while providing protection from scratches and abrasion during the handling process and from paint overspray

Recommended Application

1

Model Mask 1186 is used as received. Mix well before application.

Typically it is sprayed on the fixture using an airless sprayer, however it can be applied by air or airless spray, roll coating, or brushing.

2

Apply product evenly to produce a dry film thickness of approximately 7-10 mils or wet film thickness of 14-20 mils.

Benefits

- Water Based
- No Voc
- Removes Easily
- Can be applied to variety of substrates
- Replaces crude or ineffective liner or tape materials

Health & Safety

Handle in accordance with good industry hygiene and safety practices to minimize spill and water contamination. Refer to SDS for complete health and safety information.

Storage

Keep the containers tightly closed. Store in a cool - absolutely frost-free, dry place. Stable under normal conditions of handling and storage.

Tack Free Drying time

Drying time is dependent on temperature. At 70°F, product will dry in approximately 24 hours. You can enhance drying time by air movement and other suitable means.

Coverage

With a wet film coverage of 14-20 mils, the approximate square foot coverage of Model Mask 1186 is 78-115 sq.ft/ per gallon.

