



DeckGeneral Down Stream Injectable Deck Stripper 4167

Alkaline Deck Stripper for Down
Stream Injectors

TYPICAL PROPERTIES

Appearance= Clear to slightly
hazy liquid
pH = 13.3
VOC (EPA 24) = <0.1 lbs/gal
Density = 9.75 lbs/gal
Flashpoint = None

SHIPPING

DeckGeneral® Down Stream
Injectable Deck Stripper 4167 is
shipped in 1 gallon plastic jugs,
5 gallon plastic pails, and 55
gallon closed head plastic drums.

Description

DeckGeneral® Down Stream Injectable Deck Stripper 4167 has been formulated for use in down stream injectors. It is unique in that it takes off both oil and latex finishes and is powerful enough to remove clear and semi-transparent stains, film forming clear coatings, and water sealers. It also works on deteriorated varnishes and polyurethanes and removes damaged and discolored wood fibers, mildew and water stains, as well.

Recommended Application

- 1 Always pretest an area to be cleaned to insure compatibility with the cleaner.
- 2 DeckGeneral Down Stream Injectable Deck Stripper 4167 is used in a down stream injector.
Dilution ratio 1:10 water.
- 3 Spray cleaner on the surface to be cleaned.
- 4 Follow up with a DeckGeneral Wood Brightener to neutralize any residual stripper and to brighten the deck.

Benefits

Water based
Widespread utility
Low VOC
Concentrated formula for use in down stream injectors

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), strong acids, and soft metals, such as aluminum.

Health & Safety

Avoid contact with skin and eyes; wash thoroughly after handling. Avoid breathing vapor; use with adequate ventilation. Please refer to SDS for complete health and safety information.

Storage

KEEP FROM FREEZING! Store in a dry location at room temperature.

Keep container closed and maintain all original markings and labels. Do not use aluminum or galvanized steel for storage, pumping or transfer

Coverage

Coverage is dependent on Down Stream Injector settings; approximately 400 square feet per gallon.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com