



TYPICAL PROPERTIES

Appearance= Clear to slightly hazy liquid
pH = 13.3
VOC (EPA 24) = <0.1 lbs/gal
Density = 9.75 lbs/gal
Flashpoint = None

SHIPPING

DeckGeneral® Down Stream Injectable Deck Stripper 4167 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.

DeckGeneral Down Stream Injectable Deck Stripper 4167

Alkaline Deck Stripper for Down Stream Injectors

Description

DeckGeneral® Down Stream Injectable Deck Stripper 4167 is a professional-grade, high-alkaline liquid stripper formulated for use through a downstream injection system with pressure washers. It penetrates and breaks down weathered coatings including oil-based stains, water-based sealers, and semi-transparent wood finishes. Sodium hydroxide provides strong saponifying action to lift old coatings and contaminants in preparation for refinishing.

Recommended Application

- 1 Protect**
vegetation and adjacent surfaces; pre-wet landscaping with water.
- 2 Apply**
using downstream injector on a pressure washer (chemical draw on, water on).
- 3 Allow to Dwell**
for 10–20 minutes. Keep surface wet. Do not allow to dry on the surface.
- 4 Agitate**
using a deck brush or surface cleaner for stubborn coatings.
- 5 Rinse Thoroughly**
using high-pressure rinse.
- 6 Neutralize**
Always follow with a wood brightener to neutralize pH and restore wood color.

Benefits

Water based
Widespread utility
Low VOC
Concentrated formula for use in down stream injectors

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), strong acids, and soft metals, such as aluminum.

.....

Health & Safety

PPE Required: Wear chemical-resistant gloves, goggles, and protective clothing.

Ventilation: Use outdoors or with adequate airflow.

Avoid contact with skin and eyes; wash thoroughly after handling.

Refer to the Safety Data Sheet (SDS) for detailed safety, storage, and disposal instructions.

Storage

KEEP FROM FREEZING! Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Store tightly sealed in original container in a dry, cool, and well-ventilated area. Do not use aluminum or galvanized steel for storage, pumping or transfer.

Surfaces

Pressure-treated lumber, Cedar, redwood, pine, fir, Decks, fences, railings, log homes, siding. Note: Not for use on painted surfaces, aluminum, or softwoods without prior testing.

Applications

Removes: o Weathered oil- and water-based stains o Clear and semi-transparent wood sealers o Dirt, mold stains, and surface oxidation

Patch Test

Always test in an inconspicuous area before full application.

Disclaimer

The information provided is believed to be accurate and is offered in good faith. Suitability for specific applications must be determined by the user through proper testing. Liability is limited to replacement of defective product only.

Application

Down Stream Injectable Deck Stripper 4167 should be used as received with a downstream injector, the final dilution ratio should be 1:5-1:8 parts water.

Coverage

Coverage is dependent on Down Stream Injector settings; approximately 500-800 square feet per gallon.

.....