

**Title**

DeckGeneral® Down Stream Injectable Wood Brightener 4441

Sub Title

Phosphoric Acid Wood Brightener for Down Stream Injectors

Description

DeckGeneral® Down Stream Injectable Wood Brightener 4441 is essential for great results after using a DeckGeneral® Deck Stripper or DeckGeneral® Wood Restorer. It has been formulated to be used in a down stream injector. Treating the project with DeckGeneral® Down Stream Injectable Wood Brightener 4441 neutralizes the surface and restores the wood's natural color and beauty. Simply spray it on, let it sit five minutes and hose it off.

Typical Properties

•Appearance and odor = Clear, colorless liquid •pH = 0.75 •VOC (EPA 24) = 0.05 lbs/gal •Density = 9.8 lbs/gal •Flashpoint = None

Benefits

•Water based •Widespread utility •Low VOC •Concentrated formula for use with a down stream injector

Recommended Application

Always pretest an area to be cleaned to insure compatibility with the cleaner. DeckGeneral® Wood Brightener 4441 is diluted 1:1 with water. When diluting with water always add the product to water to avoid splashing of the alkaline solution. Apply to the area to be cleaned using a brush, roller or garden sprayer. Allow the product to soak for 5 to 10 minutes. Rinse the wood in the direction of the grain using a garden hose or a power washer at 500 to 1200 psi

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), reducing agents, bases (i.e. ammonia) and soft metals such as aluminum.

Shipping

DeckGeneral® Wood Brightener 4022 is shipped in 5-gallon plastic pails