



TYPICAL PROPERTIES

Appearance = Clear, colorless liquid
pH = 0.75
VOC (EPA 24) = 0.05 lbs/gal
Density = 9.8 lbs/gal
Flashpoint = None

SHIPPING

DeckGeneral Down Stream Injectable Wood Brightener 4441 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.

Down Stream Injectable Wood Brightener 4441

Phosphoric Acid Wood Brightener
for Down Stream Injectors

Description

DeckGeneral Down Stream Injectable Wood Brightener 4441 neutralizes the surface and restores the wood's natural color and beauty. DeckGeneral Down Stream Injectable Wood Brightener 4441 is essential for great results after using a DeckGeneral Deck Stripper or DeckGeneral Wood Restorer. It has been formulated to be used in a down stream injector.

Recommended Application

- 1 Always pretest an area to be cleaned to insure compatibility with the cleaner.
- 2 Apply to the area to be cleaned using a down stream injector.
- 3 Allow the product to soak for 5 to 10 minutes.
- 4 Rinse the wood in the direction of the grain.
Use a garden hose or a power washer at 500 to 1200 psi.

Benefits

Water based
Widespread utility
Low VOC
Concentrated formula for use with a down stream injector

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), reducing agents, bases (i.e. ammonia) and soft metals, such as aluminum.

Health & Safety

Please refer to SDS for proper safety instructions.

Application

When diluting with water, always add the product to water to avoid splashing of the alkaline solution.

