



TYPICAL PROPERTIES

- Appearance: Slight yellow to clear liquid
- Odor: odorless
- pH: 1.5- 2.0

SHIPPING

DeckGeneral® Down Stream Injectable Wood Brightener 5664 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.

DeckGeneral® Down Stream Injectable Wood Brightener 5664

Citric Acid Wood Brightener for Down Stream Injectors

Description

DeckGeneral® Down Stream Injectable Wood Brightener 5664 is essential for great results after using a DeckGeneral® Deck Stripper or DeckGeneral® Wood Restorer. It has been formulated to be used in a down stream injector. Treating the project neutralizes the surface and restores the wood's natural color and beauty.

Recommended Application

- 1 Always pretest an area to be cleaned to insure compatibility with the cleaner.
- 2 Apply Down Stream Injectable Wood Brightener 5664 to the area to be cleaned.
Down Stream Injectable Wood Brightener 5664 is used as received in a down stream injector.
- 3 Allow the product to soak for 5 to 10 minutes.
- 4 Rinse the wood in the direction of the grain.

Benefits

- Water based
- Zero VOC
- Concentrated formula for use with a down stream injector

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), reducing agents, and bases (i.e. ammonia).

Health & Safety

Avoid contact with eyes, skin, and clothing. Please refer to SDS for complete health and safety information.

Storage

Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances.

Coverage

- ⋮ Coverage is dependent on Down Stream Injector settings; approximately
- ⋮ 400 square feet per gallon.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com