Ä GENERAL CHEMICAL CORP.



TYPICAL PROPERTIES

• Appearance: Slight yellow to clear liquid

• Odor: odorless • pH: 1.5- 2.0

SHIPPING

DeckGeneral® Down Stream
Injectable Wood Brightener 5664
is shipped in 1 gallon plastic
jugs, 5 gallon plastic pails, and
55 gallon closed head plastic
drums.

DeckGeneral® Down Stream Injectable Wood Brightener 5664

Citric Acid Wood Brightener for Down Stream Injectors

Description

DeckGeneral® Down Stream Injectable Wood Brightener 5664 is essential for great results after using a DeckGeneral® Deck Stripper or DeckGeneral® Wood Restorer. It has been formulated to be used in a down stream injector. Treating the project neutralizes the surface and restores the wood's natural color and beauty.

Recommended Application

1	Always pretest an area to be cleaned
	to insure compatibility with the
	cleaner.

Apply Down Stream Injectable Wood Brightener 5664 to the area to be cleaned.

Down Stream Injectable Wood Brightener 5664 is used as received in a down stream injector.

Allow the product to soak for 5 to 10 minutes.

Rinse the wood in the direction of the grain.

Benefits

4

- •Water based
- •Zero VOC
- •Concentrated formula for use with a down stream injector

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), reducing agents, and bases (i.e. ammonia).

Health & Safety

Avoid contact with eyes, skin, and clothing. Please refer to SDS for complete health and safety information.

Storage

Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances.

Coverage

Coverage is dependent on Down Stream Injector settings; approximately 400 square feet per gallon.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600 Fax: 248-587-5606 | www.gccdatasheets.com