GENERAL CHEMICAL CORP.

DeckGeneral® Hose End Deck Cleaner 5767

Acidic Deck Cleaner for Hose End Sprayers



TYPICAL PROPERTIES

• Appearance and odor = Clear liquid
• pH =<1
• VOC (EPA 24) = 0 lbs/gal
• Density = 10.6 lbs/gal
• Flashpoint = None

SHIPPING

DeckGeneral® Hose End Deck Cleaner 5767 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.

Description

Hose-End Deck Cleaner 5767 is a ready-to-use, acid-based cleaner designed to remove dirt, rust stains, tannin discoloration, and oxidation from wood decking and outdoor surfaces. The phosphoric acid base provides powerful yet controlled cleaning action, helping to brighten weathered wood and neutralize residues from prior alkaline cleaners. The convenient hose-end sprayer provides fast and uniform coverage across large areas without the need for mixing. DeckGeneral® Hose End Deck Cleaner 5767 is a version of DeckGeneral® Deck Cleaner 4018 that has been formulated for use with a hose end sprayer.

Recommended Application

1. **Preparation**
   Rinse surrounding plants and surfaces with water.
2. **Connect**
   Attach bottle to garden hose and ensure sprayer is securely locked.
3. **Apply**
   Turn sprayer to “ON” and apply evenly to the surface.
4. **Dwell Time**
   Allow to sit for 5–10 minutes. Keep surface wet. Do not allow to dry on surface.
5. **Agitate**
   Lightly scrub with a stiff broom or brush for best results.
6. **Rinse**
   Turn sprayer to “WATER” and thoroughly rinse all surfaces.
7. **Drying**
   Allow surface to dry completely (24–48 hours) before staining or sealing.

Benefits

• Widespread utility
• Zero VOC
• Ready to use for Hose End applications

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), strong reducing agents,

strong bases (i.e. ammonia) and soft metals, such as aluminum.

Health & Safety

Personal Protection: Wear gloves and eye protection during use.
Ventilation: Use outdoors or in well-ventilated areas.
Refer to the Safety Data Sheet (SDS) for detailed handling and emergency procedures.

Storage

Keep container tightly closed in a dry, cool place. Do not expose to freezing or extreme heat.

Surfaces

Pressure-treated lumber, Cedar, redwood, pine, fir, Composite decking (spot test recommended)

Applications

Removes: o Rust and metal stains o Tannin bleed and graying from UV exposure o Alkaline residue from deck strippers o Embedded dirt and surface contaminants

Patch Test

Always test on a small, inconspicuous area to verify compatibility.

Spill Management

Neutralize with baking soda and absorb with inert material. Dispose in accordance with local regulations.

Disclaimer

The information provided is accurate to the best of our knowledge at the time of publication. Always test product for suitability before full use. Manufacturer’s liability is limited to replacement of defective product only. No other warranty is expressed or implied.

Application

Sprayer Type: Hose-end sprayer (not included)
Dilution Ratio: Automatically dilutes ~1:10 with standard garden hose

Coverage

Approximately 400 sq. ft. per gallon, depending on wood porosity and soil level.