



TYPICAL PROPERTIES

- Appearance and odor = Clear to slightly hazy liquid
- pH = 13.5
- VOC (EPA 24) = 0 lbs/gal
- Density = 10.5 lbs/gal
- Flashpoint = None

SHIPPING

DeckGeneral® Hose End Deck Stripper 5753 is shipped in 1 gallon plastic jugs, 5 gallons plastic pails, and 55 gallon closed head plastic drums.

DeckGeneral® Hose End Deck Stripper 5753

Alkaline Deck Stripper for Hose End Sprayers

Description

DeckGeneral® Hose End Deck Stripper 5753 is a version of DeckGeneral® Deck Stripper 4021 that has been formulated for use with a hose end sprayer. A heavy-duty, high-alkaline, ready-to-use formula designed to remove old or failing exterior wood finishes, including oil-based and water-based stains, clear sealers, and semi-transparent coatings. Formulated with sodium hydroxide, this product effectively breaks down finishes and wood contaminants while the hose-end sprayer ensures convenient, even application over large areas.

Recommended Application

1

Preparation

Protect surrounding vegetation and surfaces by pre-wetting or covering.

2

Connection

Attach bottle directly to a garden hose and turn on water.

3

Application

Turn dial to "ON" and spray evenly across wood surface.

4

Dwell Time

Allow product to sit for 10-15 minutes, keeping surface wet. Do not allow product to dry on surface.

5

Agitate

Use a stiff-bristle brush or deck scrubber as needed.

6

Rinse

Rinse thoroughly using hose or pressure washer (low to moderate pressure).

7

Follow-Up

Use a DeckGeneral wood brightener to neutralize the surface before staining or sealing.

Benefits

- Water based
- Widespread utility
- Zero VOC
- Ready to use for Hose End applications

.....

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), strong reducing agents, strong bases (i.e. ammonia) and soft metals, such as aluminum.

Health & Safety

PPE Required: Wear chemical-resistant gloves, safety goggles, and protective clothing.
Ventilation: Use outdoors only. Avoid inhaling mist or spray.
Refer to the Safety Data Sheet (SDS) for complete handling and emergency instructions

Storage

Keep in original container, tightly closed, in a cool, dry, and well-ventilated place. Do not freeze.

Surfaces

Pressure-treated lumber, Cedar, redwood, pine, fir, Decks, fences, siding, outdoor furniture

Applications

Removal of: Exterior wood stains (oil or water-based), Weathered sealers, Dirt, mildew stains, and surface oxidation

Patch Test

Always test in a small area before full application.

Spills

Neutralize with vinegar or citric acid and absorb with inert material.

Disclaimer

This information is believed to be accurate but is not guaranteed. Always test the product in a small, inconspicuous area to confirm suitability. Manufacturer liability is limited to replacement of defective product only.

Application

Use product as received, in a separate hose end sprayer bottle. When connected to a standard garden hose, product dilutes approximately 1:7 to 1:10 with water when spraying.

Coverage

Approximately 400 sq. ft per gallon. Actual coverage dependent on coating thickness and surface porosity.

.....