



DeckGeneral® Wood Brightener 4022

Phosphoric Acid Wood Brightener

Description

DeckGeneral® Wood Brightener 4022 is essential for great results after using a DeckGeneral® Deck Stripper or DeckGeneral® Wood Restorer. Treating the project with DeckGeneral® Wood Brightener 4022 neutralizes the surface and restores the wood's natural color and beauty. Simply spray it on, let it sit five minutes and hose it off.

TYPICAL PROPERTIES

- Appearance and odor = Clear, colorless liquid
- pH = 1.5
- VOC (EPA 24) = 0 lbs/gal
- Density = 8.6 lbs/gal
- Flashpoint = None

SHIPPING

DeckGeneral® Wood Brightener 4022 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.

Recommended Application

- 1 Always pretest an area to be cleaned to insure compatibility with the cleaner.
- 2 DeckGeneral® Wood Brightener 4022 should be diluted 1:1 with water. When diluting with water always add the product to water to avoid splashing of the alkaline solution.
- 3 Apply to the area to be cleaned using a brush, roller or garden sprayer.
- 4 Allow the product to soak for 5 to 10 minutes.
- 5 Rinse the wood in the direction of the grain using a garden hose or a power washer at 500 to 1200 psi.

Benefits

- Water based
- Widespread utility
- Low VOC

Material Compatibility

Avoid strong oxidizing agents (i.e. bleach), reducing agents, bases (i.e. ammonia) and soft metals such as aluminum.

Health & Safety

Wear chemical safety glasses with a face shield for splash protection. Please refer to SDS for complete health and safety information.

Storage

Store in cool, dry well ventilated area.

Coverage

- ⋮ One gallon of Wood Brightener 4022 provides approximately 200 square feet of coverage.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com