



### TYPICAL PROPERTIES

- Appearance and odor = Clear, blue liquid
- pH = 13.2
- VOC (EPA 24) = 0.02 lbs/gal
- Density = 9.3 lbs/gal
- Flashpoint = None

### SHIPPING

DeckGeneral® Wood Restorer Concentrate 4030 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.

# DeckGeneral® Wood Restorer Concentrate 4030

Alkaline Wood Restorer Concentrate

### Description

DeckGeneral® Wood Restorer Concentrate 4030 brings grayed and weathered wood back to its natural beauty. A professional-grade, water-based solution formulated to clean and restore exterior wood surfaces such as decks, fences, and outdoor furniture. It effectively removes grey weathering, organic stains, and surface contaminants, brightening the wood and preparing it for sealing or staining. The high-pH alkaline formula helps lift embedded soils and neutralize acidic residues.

### Recommended Application

1

#### Pre-Wet

adjacent vegetation and rinse thoroughly.

2

#### Apply

diluted solution to dry or slightly damp wood using a sprayer or brush.

3

#### Allow to Dwell

for 5-15 minutes. Do not let dry on the surface.

4

#### Scrub

with a stiff-bristle brush or agitate with a power washer (low pressure).

5

#### Rinse Thoroughly

with clean water.

6

#### Allow wood to dry 24-48 hours

before sealing or staining.

### Benefits

- Water based
- Widespread utility
- Zero VOC

### Health & Safety

PPE: Use chemical-resistant gloves, eye protection, and appropriate clothing.

Ventilation: Use outdoors or in well-ventilated areas.

Avoid contact with skin and eyes; wash thoroughly after handling. Please refer to SDS for complete health and safety information.

### Storage

KEEP FROM FREEZING! Store in a dry location at room temperature.

Keep container closed in a dry, cool, well-ventilated place. Refer to the Safety Data Sheet (SDS) for full handling and safety instructions.

**Surfaces**

Pressure-treated lumber, Cedar, redwood, and pine

**Applications**

□ Restoration of weathered wood □ Pre-treatment before sealing or staining □ Removal of: o Dirt, mold, and algae stains o Tannin bleeding and water marks o Oxidized and grey wood fibers

**Patch Test**

Always pretest an area to be cleaned to insure compatibility with the cleaner.

**First - Aid**

In case of contact, rinse with water. Seek medical attention if irritation persists.

**Disclaimer**

All information provided is based on laboratory testing and field use under normal conditions. It is the responsibility of the end user to determine product suitability for specific applications. No warranty is expressed or implied beyond replacement of defective product.

**Application**

DeckGeneral® Wood Restorer Concentrate 4030 is mixed equal parts with water. When diluting with water always add the product to water to avoid splashing of the alkaline solution.

**Coverage**

Approximately 150–300 sq. ft. per gallon of diluted solution, depending on wood porosity and condition.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)