

# DeckGeneral® Wood Restorer Concentrate 4030

Alkaline Wood Restorer Concentrate

## TYPICAL PROPERTIES

•Appearance and odor = Clear, blue liquid •pH = 13.2 •VOC (EPA 24) = 0.02 lbs/gal •Density = 9.3 lbs/gal •Flashpoint = None

## SHIPPING

DeckGeneral® Wood Restorer Concentrate 4030 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.

## Description

DeckGeneral® Wood Restorer Concentrate 4030 brings grayed and weathered wood back to its natural beauty. DeckGeneral® Wood Restorer Concentrate 4030 quickly removes damaged and discolored wood fibers, tannin stains, mildew and water stains from surfaces that have little or no finish remaining.

## Recommended Application

1

Always pretest an area to be cleaned to insure compatibility with the coating. DeckGeneral® Wood Restorer Concentrate 4030 is mixed equal parts with water. When diluting with water always add the product to water to avoid splashing of the alkaline solution. Apply to the area to be cleaned using a brush, roller or garden sprayer. Allow the product to soak for 5 to 10 minutes. Mild scrubbing can be performed to increase effectiveness. Rinse the wood in the direction of the grain using a garden hose or a power washer at 500 to 1200 psi. Coverage is 150 to 300 square feet per gallon. Please refer to the MSDS for proper safety instructions.

Always pretest an area to be cleaned to insure compatibility with the coating. DeckGeneral® Wood Restorer Concentrate 4030 is mixed equal parts with water. When diluting with water always add the product to water to avoid splashing of the alkaline solution. Apply to the area to be cleaned using a brush, roller or garden sprayer. Allow the product to soak for 5 to 10 minutes. Mild scrubbing can be performed to increase effectiveness. Rinse the wood in the direction of the grain using a garden hose or a power washer at 500 to 1200 psi. Coverage is 150 to 300 square feet per gallon. Please refer to the MSDS for proper safety instructions.

## Benefits

•Water based •Widespread utility •Zero VOC

## Material Compatibility

Avoid strong acids, flammable liquids, organic halogens and soft metals, such as aluminum.

