

## **Product Information**

**Description** - PaverGeneral® Masonry Sealer 5745 is an acrylic based sealer that leaves a glossy finish on paving bricks and stones, while also providing water repellency. PaverGeneral® Masonry Sealer 5745 has a higher actives level than PaverGeneral® Masonry Sealer 4551.

**Sub Title** - Acrylic Sealer

**Typical Properties** - •Appearance and odor = Clear, colorless liquid with a solvent odor •pH = N/A •VOC (EPA 24) = 5.75 lbs/gal •Density = 7.65 lbs/gal •Flashpoint = 111 °F

**Benefits** - •Quick drying time •Glossy finish •Water repellency

**Recommended Application** - The surface should be free of standing water and surface dirt. All nearby vegetation and any material that is not to be treated should be protected. For previously sealed surfaces, apply one heavy coat. For unsealed surfaces, apply two coats. The first coat should be a light coating that will dry in a short time, followed by a second heavy coat. Methods of application include airless sprayer, roller and brush. When a brush or roller is used, repeat application until the surface remains moist for a few minutes. If an airless sprayer is used, apply the material until the substrate is thoroughly saturated. Please refer to the MSDS for proper safety instructions.

**Material Compatibility** - PaverGeneral® Masonry Sealer 5745 is combustible. Avoid contact with heat, sparks and open flames.

**Shipping** - PaverGeneral® Masonry Sealer 5745 is shipped in 1 gallon plastic jugs, 5 gallon plastic pails, and 55 gallon closed head plastic drums.