

#### **TYPICAL PROPERTIES**

- •Appearance and odor = Silver, gray liquid with a solvent odor •pH = NA
- •VOC (EPA 24) = 5.7 lbs/gal
- Density = 6.15 lbs/gal
- •Flashpoint = 20 °F

# FoundryGeneral® No Bake Release 5000

Aluminum No Bake Release Agent

### **Description**

FoundryGeneral® No Bake Release 5000 is a release agent that has been formulated specifically for the No-Bake process. FoundryGeneral® No Bake Release 5000 utilizes aluminum flake and silicone fluid to form a superior release film.

## **Recommended Application**

FoundryGeneral® No Bake Release 5000 is used as received.

It must be mixed or shaken prior to use, as it tends to separate on standing.

FoundryGeneral® No Bake Release 5000 can be sprayed or brushed lightly onto tooling.

#### **Benefits**

- Better core definition
- Cores strip much easier
- Safe for use on foam molds
- Rapid drying

## **Material Compatibility**

Product is extremely flammable. Keep away from all ignition sources. Avoid heat, sparks and open flames. Avoid strong oxidizing agents (i.e. bleach).

## **Health & Safety**

Please refer to SDS for complete health and safety information.

# Storage

With proper storage, shelf life is 1 year from date of manufacture. Please refer to SDS for complete storage information.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600 Fax: 248-587-5606 | www.gccdatasheets.com