

# FoundryGeneral® Green Sand Parting 102

Oil Based Green Sand Parting

## TYPICAL PROPERTIES

- Appearance and odor = Clear, colorless to light amber liquid
- pH = NA
- VOC (EPA 24) = Not determined
- Density = 7 lbs/gal
- Flashpoint = 265 °F

## SHIPPING

FoundryGeneral® Green Sand Parting 102 is shipped in metal pails and drums.

## Description

FoundryGeneral® Green Sand Parting 102 is low viscosity parting designed for particularly for automatic high production molding machines.

## Recommended Application

1

FoundryGeneral® Green Sand Parting 102 is used as received.

Prior to application, patterns should be well cleaned of previous release agents and dirt through the use of a solvent.

2

A light film of FoundryGeneral® Green Sand Parting 102 should be applied by spraying a mist onto the pattern.

Avoid using too much, as it will eventually lead to a sticky film.

3

Reapply as needed.

## Benefits

- Inhibits corrosion of metal patterns
- Will not build up on metal patterns unless too much is used
- Will not attack the sand clay bond when used as recommended
- If sprayed every mold cycle, less parting is needed per mold

## Material Compatibility

Avoid heat, sparks and open flames. Avoid strong oxidizing agents (i.e. bleach)

## Health & Safety

Please refer to SDS for complete health and safety information.

## Storage

With proper storage, shelf life is 6 months from date of manufacture. Please refer to SDS for complete storage information.