

FoundryGeneral® Green Sand Parting 103

Oil Based Green Sand Parting

Description

FoundryGeneral® Green Sand Parting 103 is an economically priced parting for automatic molding machines. FoundryGeneral® Green Sand Parting 103 is typically sprayed every cycle.

Recommended Application

1

FoundryGeneral® Green Sand Parting 103 is used as received.

Prior to application, patterns should be well cleaned of previous release agents and dirt through the use of a solvent.

2

A light film of FoundryGeneral® Green Sand Parting 103 should be applied by spraying a mist onto the pattern.

Avoid using too much, as it will eventually lead to a sticky film. Reapply as needed.

Benefits

- Inhibits corrosion of metal patterns
- Will not build up on metal patterns unless too much is used
- Will not attack the sand clay bond when used as recommended
- If sprayed every mold cycle, less parting is needed per mold

Material Compatibility

Avoid heat, sparks and open flames. Avoid strong oxidizing agents (i.e. bleach) and strong acids.

Health & Safety

Please refer to SDS for complete health and safety information.

TYPICAL PROPERTIES

- Appearance and odor = Clear, colorless to light amber liquid
- pH = NA
- VOC (EPA 24) = Not determined
- Density = 7.15 lbs/gal
- Flashpoint = 145 °F

SHIPPING

FoundryGeneral® Green Sand Parting 103 is shipped in metal pails and drums

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com