

FoundryGeneral® Pattern Spray 1

Pattern Spray

TYPICAL PROPERTIES

- Appearance and odor = Clear, colorless to light amber liquid
- pH = NA • VOC (EPA 24) = 3.05 lbs/gal
- Density = 7.05 lbs/gal
- Flashpoint = 270 °F

SHIPPING

FoundryGeneral® Pattern Spray 1 is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

Description

FoundryGeneral® Pattern Spray 1 is an oil based liquid parting for use on all molding lines.

Recommended Application

1

FoundryGeneral® Pattern Spray 1 is used as received. It should be sprayed onto the working surface with an atomizing sprayer. Please refer to the MSDS for proper safety instructions. FoundryGeneral® Pattern Spray 1 is used as received. It should be sprayed onto the working surface with an atomizing sprayer. Please refer to the MSDS for proper safety instructions.

Benefits

- Multiple partings per application
- Minimal build up
- Will not attack tooling surfaces

Material Compatibility

Avoid heat, sparks and open flames. Avoid strong oxidizing agents (i.e. bleach).

Storage

With proper storage, shelf life is 1 year from date of manufacture. Please refer to SDS for complete storage information.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com