

TYPICAL PROPERTIES

- •Appearance and odor = Milky white, opaque liquid
- \bullet pH = 8
- •VOC (EPA 24) = 3.1 lbs/gal
- Density = 7.7 lbs/gal
- •Flashpoint = None °F

SHIPPING

FoundryGeneral® Pattern Spray WEB is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

FoundryGeneral® Pattern Spray WEB

Pattern Spray Emulsion

Description

FoundryGeneral® Pattern Spray WEB is an oil in water emulsion for use parting on all molding lines.

Recommended Application

FoundryGeneral® Pattern Spray WEB is used as received.

It should be sprayed onto the working surface with an atomizing sprayer.

Benefits

- •Water based
- •Minimal build up
- •Will not attack tooling surfaces
- $\bullet \text{Multiple partings per application} \\$

Material Compatibility

Avoid heat, sparks and open flames. Keep from freezing. Avoid strong oxidizing agents (i.e. bleach).

Health & Safety

Please refer to SDS for complete health and safety information.

Storage

With proper storage, shelf life is 6 months from date of manufacture. Please refer to SDS for complete storage information.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600 Fax: 248-587-5606 | www.gccdatasheets.com