



TYPICAL PROPERTIES

- Appearance: Amber liquid
- pH: 10.0 - 11.0
- Specific gravity: 1.04-1.06

STRIPOXY 9850

Water Based Paint Stripper For
Soak Tank

Description

StripOxy 9850 is a multi-metal safe, concentrated, water based paint strip solution formulated to delaminate cured coatings, including: powder coating, e-coating and wet-applied cured coatings.

Recommended Application

1

Utilize an immersion strip tank with lid and proper ventilation.

2

Immerse parts to be stripped in StripOxy 9850 at 50% concentrated water.

3

Heat to 160-185°F.
Heat helps in faster release of an adhesive or coatings from base substrate. Replenish loss solution as needed.

4

Rinse parts with fresh water with a pressure washer.

Health & Safety

Avoid breathing in vapors, wear respirator if necessary. May be harmful if swallowed. May cause skin and eye irritation. Eye protection and rubber gloves are recommended when handling this product. Please refer to SDS for complete health and safety information.

Storage

Store in dry and ventilated area. Keep containers closed when not in use. Do not store with strong bases or oxidizing agents.

Application

Maximum amount of time a substrate should be left in stripping solution: overnight.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com