

BOOTHCOAT 5201

PEELABLE COATING

TYPICAL PROPERTIES

Color: White
Weight: 9.3 lbs/gallon
Viscosity: 8,000-14,000 centipoise
Flashpoint: None

SHIPPING

Boothcoat 5201 is shipped in 1 gallon metal cans, 5 gallons plastic buckets, or 55 gallon open head plastic drums.

Description

Booth Coat 5201 is a white water-based, one-pack, temporary coating which provides easy peel. Boothcoat 5201 is a temporary peelable coating for paint spray-booth walls, ceilings, floors and other surfaces where paint over spray accumulation must be readily removed. Boothcoat 5201 can be used as a peelable coating on steel surfaces to eliminate flash rusting or as protection on glass, plexiglass, rubber, cement, aluminum and many other hard surfaces. It is well stabilized against brittleness and it will not be softened or penetrated by most solvent-based paints.

Recommended Application

1

It should be used as received. It can be applied by spray, roller (1/8" nap works best) or brush. Apply at temperatures over 50F. Humidity will effect dry times. Apply a minimum of 8 mils (.008) of wet film. For best results should be applied at 45F to 100F and low humidity. Boothcoat 5201 optimum in temperature above 40F/5C.

It should be used as received. It can be applied by spray, roller (1/8" nap works best) or brush. Apply at temperatures over 50F. Humidity will effect dry times. Apply a minimum of 8 mils (.008) of wet film. For best results should be applied at 45F to 100F and low humidity. Boothcoat 5201 optimum in temperature above 40F/5C.

Benefits

Multifunctional products.
Efficient delivery systems that make it economical to treat hard-to-protect items.
Easy application.
Zero VOC

Removal and curing

Boothcoat 5201 can be removed by peeling. The dry coating is disposed like paint films and other solid materials .