

# GRATE COATING-1775

GC-1775

## TYPICAL PROPERTIES

- Appearance: White, viscous liquid
- pH = 8.5 - 9.5
- VOC (EPA 24) = < 0.3 lbs/gal
- Viscosity: 5,000 - 10,000 cps
- Flashpoint = None to boiling
- Specific Gravity: 1.33 - 1.34

## SHIPPING

Grate Coating 1775 is shipped in 1 gallon metal cans, 5 gallon plastic buckets, or 55 gallon open head plastic drums.

## Description

Grate Coating 1775 is a water based, fast drying, white grate coating that has been formulated with special resins to provide a hard, non-chalking barrier. It is used to protect paint booth grates, floors, and walls. Grate Coating 1775 is an effective barrier for most paints, adhesives, waxes, and greases, or oils.

## Recommended Application

1

Grate Coating 1775 can be sprayed, brushed, or rolled onto the surface to be coated.

A coating of 1-2 mils is usually sufficient to give protection against most paints and adhesives.

2

Allow drying time.

Drying time is 0.5 to 1.0 hour depending on the atmospheric conditions at the time of application.

3

Grate Coating 1775 is easily removed with a stream of water.

Increasing water pressure facilitates removal as does soaking with water before spraying

## Benefits

- Water Based
- Water Rinsable
- Non-Chalking
- Rapid Drying
- Low VOC

## Health & Safety

Please refer to SDS for complete health and safety information.

## Storage

Product has a shelf life of 6 months from manufacture date.

## Tack Free Drying time

Drying time is 0.5 to 1.0 hour depending on the atmospheric conditions at the time of application.

## Removal

Grate Coating 1775 is removed with water.

