

GRATE COATING-1775

GC-1775

TYPICAL PROPERTIES

- Appearance: White, viscous liquid
- pH = 8.5 - 9.5
- VOC (EPA 24) = < 0.3 lbs/gal
- Viscosity: 5,000 - 10,000 cps
- Flashpoint = None to boiling
- Specific Gravity: 1.33 - 1.34

SHIPPING

Grate Coating 1775 is shipped in 1 gallon metal cans, 5 gallon plastic buckets, or 55 gallon open head plastic drums.

Description

Grate Coating 1775 is a water based, fast drying, white grate coating that has been formulated with special resins to provide a hard, non-chalking barrier. It is used to protect paint booth grates, floors, and walls. Grate Coating 1775 is an effective barrier for most paints, adhesives, waxes, and greases, or oils.

Recommended Application

1

Grate Coating 1775 can be sprayed, brushed, or rolled onto the surface to be coated.

A coating of 1-2 mils is usually sufficient to give protection against most paints and adhesives.

2

Allow drying time.

Drying time is 0.5 to 1.0 hour depending on the atmospheric conditions at the time of application.

3

Grate Coating 1775 is easily removed with a stream of water.

Increasing water pressure facilitates removal as does soaking with water before spraying

Benefits

- Water Based
- Water Rinsable
- Non-Chalking
- Rapid Drying
- Low VOC

Health & Safety

Please refer to SDS for complete health and safety information.

Storage

Product has a shelf life of 6 months from manufacture date.

Tack Free Drying time

Drying time is 0.5 to 1.0 hour depending on the atmospheric conditions at the time of application.

Removal

Grate Coating 1775 is removed with water.

