



TYPICAL PROPERTIES

Appearance Form: Brown liquid
Odor: Mild Odor
pH: 3-4

SHIPPING

Stripoxy 6840 is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

STRIPOXY 6840

Water Based Epoxy Paint Remover

Description

Stripoxy 6840 is used for paint removal of cured & uncured epoxy coatings from a variety of substrates. Stripoxy 6840 is specifically designed for aluminum and non ferrous metals. Stripoxy 6840 can also be used as an adhesive remover and urethane paint stripper. Stripoxy 6840 is non-flammable in nature. Low vapor pressure radically reduces VOC emissions. Ideal for soak tank application.

Recommended Application

- 1 Stripoxy 6840 is engineered for soak tank applications.
- 2 Dilute with 50% water. Use from 140°F to 185°F.

Benefits

Superior cleaning ability
Low foaming
Does not contain phenols, chlorinated or flammable solvents
Water based product
Works well on coated carbon steel, stainless steel and aluminum

Material Compatibility

Safe for use on non-ferrous metals. *Please use extra caution as it can be damaging to certain Magnesium alloys

Health & Safety

Please refer to SDS for complete health and safety information.

Storage

Stripoxy 6840 has a shelf life of 1 year from date of manufacture.

Comparable Products

StripOxy 6840 is a less potent version of StripOxy 6842.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com