

# STRIPOXY 6840

Water Based Epoxy Paint Remover



## TYPICAL PROPERTIES

Appearance Form: Brown liquid  
Odor: Mild Odor  
pH: 3-4

## SHIPPING

Stripoxy 6840 is shipped in 1 gallon plastic jugs, 5 gallon plastic buckets, or 55 gallon closed head plastic drums.

## Description

Stripoxy 6840 is used for paint removal of cured & uncured epoxy coatings from a variety of substrates. Stripoxy 6840 is specifically designed for aluminum and non ferrous metals. Stripoxy 6840 can also be used as an adhesive remover and urethane paint stripper. Stripoxy 6840 is non-flammable in nature. Low vapor pressure radically reduces VOC emissions. Ideal for soak tank application and also for spray application.

## Recommended Application

- 1 Stripoxy 6840 is engineered for soak tank and spray applications.
- 2 Dilute with 50% water. Use from 140°F to 185°F.

## Benefits

- Superior cleaning ability
- Low foaming
- Does not contain phenols, chlorinated or flammable solvents
- Water based product
- Works well on coated carbon steel, stainless steel and aluminum

## Health & Safety

Please refer to SDS for complete health and safety information.

## Storage

Stripoxy 6840 has a shelf life of 1 year from date of manufacture.

## Comparable Products

StripOxy 6840 is a less potent version of StripOxy 6842.