



### TYPICAL PROPERTIES

Appearance and odor = Clear to slightly translucent liquid with a mild odor.

pH = 9.4 - 9.9

VOC (EPA 24) = 0 lbs/gal

Viscosity: 1,500 - 3,000 cps

Flashpoint = None to boiling (Pensky-Martens)

Specific Gravity: 1.01 - 1.02

Max Operating Temperature: 120°F

### SHIPPING

Boothcoat 1700 is shipped in 1 gallon metal cans, 5 gallon plastic buckets, or 55 gallon open head plastic drum.

# BOOTHCOAT 1780

## CLEAR BOOTH COATING

### Description

BoothCoat 1780 is a water based, fast drying, coating that has been formulated with special resins to provide a hard, clear barrier. It is used to protect paint booth grates, floors and walls. BoothCoat 1780 is an effective barrier for most paints, adhesives, waxes, greases and oils.

### Recommended Application

1

Ensure surface is clean and free of debris.

2

Apply with spray, brush, or roller to 3 to 6 mils wet.

3

Remove with water when ready.

### Benefits

- Water Based and Water Rinse-able
- Provides a clear, hard film
- Rapid Drying
- Easily Applied
- No VOC

### Health & Safety

Please refer to SDS for proper safety instructions.

### Storage

Shelf life is 1 year from date of manufacture.

### Application

Airless sprayer with .015 to .019 tip is recommended.

### Tack Free Drying time

Drying time is 0.5 to 1.0 hour depending on the atmospheric conditions at the time of application.

### Coverage

When applied to 6 mils wet film, 1 gallon of BoothCoat 1780 provides approximately 260 square feet of coverage.

### Removal

BoothCoat 1780 is easily removed with a stream of water. Increasing water pressure facilitates removal as does soaking with water before spraying.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)