

# Vinyl Siding Cleaner 50162

Vinyl Siding Cleaner



## TYPICAL PROPERTIES

Appearance : Thick, clear, colorless to amber liquid  
Odor: Mild odor  
Weight: 8.8lbs/gal  
Flash point: None  
VOC: 0.4lbs/gal  
pH: 12

## SHIPPING

Shipped in 1 Gallon Plastic Jug, 5 Gallon Plastic Bucket, and 55 Gallon Closed Head Plastic Drum.

## Description

Vinyl Siding Cleaner 50162 is a unique concentrated siding cleaner that is nonflammable and low VOC. It contains a blend of specialty surfactants, detergents, and emulsifiers that effectively penetrate the toughest stains from dirt, oil, grease, and bird droppings. Its thickened formulation provides excellent vertical retention, which increases the products contact time on the soiled surface. Vinyl Siding Cleaner 50162 is safe, fast, and effective on roofing, gutters, fencing, stucco, bricks, cement block, masonry, concrete, driveways, walkways and walls, and even patio furniture. Vinyl Siding Cleaner 50162 does not contain petroleum solvents, bleach, or ammonia.

## Recommended Application

1

**Pre-Wet**  
surfaces and surrounding vegetation with water.

2

**Apply**  
diluted solution using a pump sprayer, brush, or chemical injector on a pressure washer.

3

**Allow to Dwell**  
for 5-10 minutes. Do not allow to dry on the surface.

4

**Agitate**  
lightly with a soft brush or sponge if needed.

5

**Rinse Thoroughly**  
with clean water under moderate pressure.

6

**Repeat**  
if necessary for stubborn oxidation or heavy soil buildup.

## Benefits

- Effective resin removal
- Non-chlorinated
- High flash point

## Material Compatibility

Not recommended for: Unsealed wood, glass, or polished stone without prior testing.

## Health & Safety

PPE: Wear chemical-resistant gloves, eye protection, and protective clothing.  
Ventilation: Use in well-ventilated areas or outdoors.  
Spill Management: Absorb with inert material and dispose per local

regulations.  
Please refer to the SDS for proper safety instructions.

**Storage**

Store in a cool, dry location away from heat and direct sunlight.

**Surfaces**

Exterior vinyl siding (all colors), Aluminum, painted metal, and fiberglass siding, Gutters, soffits, and trim

**Applications**

□ Exterior vinyl siding (all colors) □ Aluminum, painted metal, and fiberglass siding □ Gutters, soffits, and trim □ Pre-paint cleaning □ Pressure washing systems

**Patch Test**

Always test for surface compatibility, with the cleaner, in an inconspicuous area prior to use.

**Regulatory Compliance**

CAS Numbers: Glycol Ether EB: 111-76-2 Sodium Metasilicate: 6834-92-0  
VOC Compliance: Meets most U.S. state and federal VOC requirements for exterior cleaners. EPA Status: Not registered as a pesticide. Contains no bleach, ammonia, or petroleum distillates.

**Disclaimer**

This information is offered in good faith and believed to be accurate at the time of publication. Product performance should be verified by the end user under specific application conditions. Manufacturer’s liability is limited to product replacement only.

**Application**

Use 1 part cleaner to 10 parts water or 1 part cleaner to 5 parts water for heavier soils.  
Always work on a section of siding from bottom to top, and always work in the shade. You never want the soapy water to dry on the siding before it can be rinsed off.

**Coverage**

150-300 sq. ft. per gallon of diluted solution, depending on surface condition and method.

**Clean Down**

Rinse equipment and brushes thoroughly with water.