



### TYPICAL PROPERTIES

Appearance: Light amber, viscous liquid  
Flash Point: 145°F (minimum)  
Specific Gravity: 0.99  
Viscosity: 700 - 1,000 cps

# Paint Line Cleaner 47-LT-1

## PAINT BOOTH CLEANER

### Description

PC-47-LT-1 is a water rinsable solvent based cleaner that has been formulated to provide effective removal of paint overspray from booth walls and windows that have been exposed to two component (2K) clear coats. The viscosity of the product has been adjusted to provide excellent vertical surface retention. The chemical composition of this formulation has been selected to provide effective paint removal while minimizing employee and environmental dangers.

### Recommended Application

1

PC-47-LT-1 can be sprayed or manually applied by brush.

A uniform application will insure more consistent performance. The amount of material required, setting time, and the amount of mechanical agitation needed will depend upon the severity of the build-up and the plants' operational constraints.

2

Rinsing of this product can be accomplished using either high or low pressure water spray.

In cases of severe build-up or extended exposure times, high pressure water rinse will yield better results.

### Benefits

- Excellent viscosity stability
- Easily rinsed from all surfaces

### Health & Safety

Avoid contact with skin and eyes; wash thoroughly after handling. Avoid breathing vapor; use with adequate ventilation. Please refer to SDS for complete health and safety instructions.

### Storage

Do not use aluminum or galvanized steel for pumping, storage, or transfer. Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels.