

# PaintShield 5140

Peelable Coating



## TYPICAL PROPERTIES

- Color: clear
- Weight: 8.87 lbs/gallon
- Viscosity: 50-60 sec on Zahn 4 cup
- Flashpoint: None

## SHIPPING

Paintshield 5140 is shipped in 1 gallon metal cans, 5 gallon plastic buckets, or 55 gallon open head plastic drums.

## Description

Temporary, protective automotive peelable masks for protecting automobile designed to combat the hazards that a vehicle faces on today's highways. Rock chips, insects, bad weather, and salted roadways are just some of the things that can damage the beautiful factory finish of a vehicle and diminish its value. Paintshield 5140 represents the ultimate in non-solvent peelable coatings. It is well stabilized against brittleness and it will not be softened or penetrated by most solvent-based paints. Paintshield 5140 has no VOC's.

## Recommended Application

1

Paintshield 5140 is normally used as received.

It is applied by airless spray, roller or brush.

2

Paintshield 5140 is applied to form a film thickness in the range of 2 to 5 mils (.002" to .005").

3

The sprayed peelable coating air-dries in 10 minutes to 3 hours, depending on thickness of the coating, humidity, temperature and air movement.

Application temperature is ambient to no lower than 60° F. Humidity will effect dry times.

## Benefits

- Multifunctional product.
- Effective protection.
- Efficient delivery systems that make it economical to treat hard-to-protect items.
- Easy application.
- Improved health, safety, and pollution control.
- Elimination of extra processing steps in most cases

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)