



TYPICAL PROPERTIES

Appearance: Thick, white grease
Specific Gravity: 0.9-0.92
Grease Penetration: 32-37 mm
Max. Operating Temperature:
100°F

SHIPPING

Booth Coat 4568 is shipped in 1 gallon metal cans, 5 gallon metal pails, or 55 gallon open head metal drums.

Booth Grease 4568 (White)

GREASE BOOTH / BAFFLE
COATING

Description

Booth Grease 4568 has been formulated for application to baffles, back sections, stacks, underbooth areas, and other locations where a greasy coating is desired to prevent adhesion of paint overspray. It is water resistant and has good adhesion to vertical surfaces. Petroleum based.

Recommended Application

1

Booth Grease 4568 is applied by 30:1 airless spray.
It can also be applied by brush, roll, or trowel.

2

Remove by scraping after painting operations are completed.

Benefits

Facilitates easier future clean outs
Easily removed by scraping
Easy application

Health & Safety

Please refer to SDS for complete health and safety information.

Storage

Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Do not reuse container without recycling or reconditioning. Handle empty containers as if they were full.

Removal

The protective barrier of Booth Coat 4568 is easily removed with scraping, as the coating remains soft and can be scraped with minimal effort.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com