

# Stripaway 5980

Peelable Coating



## TYPICAL PROPERTIES

Appearance: Translucent white when cured  
VOC: None

## SHIPPING

Stripaway 5980 is available in 1 gallon cans, 5 gallon pails, and 55 gallon drums.

## Description

Stripaway 5980 is a water-based peelable coating, which provides temporary protection of semi and fully glazed wood, weather coated or as such from damage, scratches, chipping, and from exterior and/or interior environmental factors. The coating can also protect surfaces from paint overspray or damage during manufacturing and shipping. Stripaway 5980 represents the ultimate in non-solvent, water borne, strippable coatings.

## Recommended Application

- 1 Perform patch test.
- 2 Stripaway 5980 is used as received. It is applied by airless spray, roller or brush.
- 3 Apply a minimum of 10 mils of wet film.
- 4 Stripaway 5980 cures upon water evaporation.
- 5 Stripaway 5980 is removed by peeling.

## Benefits

- Virtually eliminates repairs caused during construction
- Provides temporary protection through inspection
- Replace crude and ineffective liner materials

## Health & Safety

Please refer to SDS for complete health and safety information.

## Storage

Store at temperatures between 5°C - 25°C. DO NOT ALLOW LIQUID TO FREEZE. Product has shelf life of 1 year from date of manufacture.

## Patch Test

Because it is difficult to determine the type of substrate, perform a small test first. This will determine effectiveness, coverage, and the approximate amount of time required for it to work.

## Tack Free Drying time

The cure process can be within 30 minutes or if humid can take hours. Factors effecting cure are temperatures, humidity and thickness of

coating. Curing may be accelerated by forced drying at 110 - 130 degrees Fahrenheit for 3 to 7 minute

### **Coverage**

When applied to a thickness of 10 mils wet film, 1 gallon of Stripaway 5980 will provide approximately 200 square feet of coverage.

### **Removal**

Stripaway 5980 can be removed by peeling. Stripaway 5980 is disposed like paint films and other solid materials.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)