

Tacky Booth Coat 2769

WHITE TACKY BOOTH COATING



TYPICAL PROPERTIES

- Appearance: White, viscous liquid
- pH = 7.5 - 8.5
- VOC (EPA 24) = 2.0 - 4.0 lbs/gal
- Flashpoint = None to boiling
- Specific Gravity: 1.16 - 1.22
- Viscosity: 20,000-30,000 cps

Description

Tacky Booth Coat 2769 is a white, soft, tacky booth coating that is used to protect interiors of paint booths from contamination due to paint overspray. It is water base with a low VOC and compatible with all paint detackification processes. Tacky Booth Coat 2769 imparts a lustrous white surface to booth walls and floors while remaining wet and tacky to attack airborne dust and dirt. It can be removed with a water rinse or scraping.

Recommended Application

1

Ensure surface is clean and free of debris.

2

Tacky Booth Coat 2769 can be brushed or rolled onto surface to be coated.

The product should be applied as received without thinning.

3

A coating of 8-10 mil is generally sufficient to protect most surfaces.

Benefits

- Low VOC
- Water Based
- Scrapable
- Excellent Tack
- User Friendly

Health & Safety

Avoid contact with skin and eyes; wash thoroughly after handling. Please refer to SDS for complete health and safety information.

Storage

KEEP FROM FREEZING! Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Shelf life: 6 months from date of manufacture. Storage conditions may affect the shelf life.

Application

Tacky Booth Coat 2769 may also be sprayed with correct sprayer type.

Coverage

Depending on thickness applied, 1 gallon of Tacky Booth Coat 2769 can provide 200 square feet of coverage.

Removal

- ⋮ The product can be easily removed with a scraper or with a water rinse.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com