



### TYPICAL PROPERTIES

- Appearance: Clear, thick liquid with a citrus odor.
- Flashpoint: 200°F
- VOC: 2.6 lbs/gal
- pH: 10.65

### SHIPPING

Ships in 1 Gallon Plastic Jug, 5 Gallon Plastic Bucket, 55 Gallon Closed Head Plastic Drum

# Paint Booth Stripper 5771

## Water Based Paint Stripper

### Description

Paint Booth Stripper 5771 is a thickened, water based cleaner designed to remove paint over spray and deposits from booth walls and equipment. This paint stripper is a specially formulated water based, thixotropic liquid gel paint remover for the cost effective and environment friendly paint removal of uncured and old cured paints and coatings such as epoxies and urethane materials from concrete, aluminum and other non ferrous alloys, wood, and masonry substrates. Paint Booth Stripper 5771 effectively removes latex, alkyd, acrylic paints, and many other high performance coatings such as two component epoxy and urethane. This product contains no known carcinogens, methylene chloride or other chlorinated solvents.

### Recommended Application

1

Paint Booth Stripper 5771 can be sprayed or manually applied by brush. A uniform application will insure more consistent performance.

2

Rinsing of this product can be accomplished using either high or low pressure water spray.

### Benefits

- Water Based
- Extremely effective
- Safe & Easy to Use
- Excellent viscosity

### Health & Safety

Avoid contact with skin and eyes; wash thoroughly after handling. Avoid breathing vapor; use with adequate ventilation. Refer to SDS for complete health and safety information.

### Storage

Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels.

### Application

A uniform application will insure more consistent performance. The amount of material required and the penetration time will depend upon the severity of the build-up and the plants' operational constraints.

### Removal

Rinsing of this product can be accomplished using either high or low-pressure water spray. In cases of severe build-up or extended exposure times, high pressure water rinse will yield better results.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600  
Fax: 248-587-5606 | [www.gccdatasheets.com](http://www.gccdatasheets.com)