A GENERAL CHEMICAL CORP.



TYPICAL PROPERTIES

- Appearance: White liquid with a slight acrylic odor

- pH: 6-8

CarpetGeneral Carpet Stain Guard 5816

Carpet & Upholstery Protector, Stain Repellent

Description

Carpet Stain Guard 5816 is a ready to use water based carpet and upholstery protector that when applied after carpet cleaning forms an invisible shield around each fiber to resist soil and stains. Designed to replace or enhance any of the built-in stain resist properties of the carpet that may have been removed during the wet cleaning process or worn off by normal abrasion (foot traffic, vacuuming, etc.) Carpet Stain Guard 5816 provides superior repellency and outstanding soil protection for all types of residential carpet and helps carpets stay cleaner, brighter, newer and fresher through all kinds of daily wear! It may also be applied to water safe upholstery and drapery fabrics.

Recommended Application

4	Always pretest an area to be cleaned
1	to insure compatibility with the
	cleaner.

2 Apply solution with a spray bottle.

Spray a fine mist and thoroughly cover the

Let applied area dry for a minimum of one hour for maximum protection against spills, soils, and stains.

Benefits

- Easily applied using an in-line sprayer; no dilution or mess.
- Helps protect against both oil- and water-based stains.
- Superior repellency to clean up spills before they sink in
- Ideal for carpet, rugs, stairways, hallway and stairway runners, bath mats, drapery, and more

Material Compatibility

In general, Carpet Stain Guard 5816 can be used on cotton, polyester, silk, wool, acrylic, nylon, and most other washable fabrics. Do not use on "X" coded fabric (fabric that cannot be cleaned with water or solvents). You can find this code on the tag sewn into your fabric item. It is always best to test on a small, out-of-the-way spot first to make sure your fabric will stay colorfast.

Health & Safety

Follow safe industrial hygiene practices and wear proper protective equipment. Use only in well ventilated areas. Wash hands thoroughly after handling. Please refer to SDS for complete health and safety information.

Storage

Store material at -5 C (23 F) to 40 C (104 F). Keep away from heat, steam, sunlight, sparks and open flame. Store containers tightly closed when not in use

Reapplication

Duration of protection is dependent on the amount of traffic the surface receives. Stain Guard should be reapplied after 6 months or after every extraction cleaning.

Application

Do not over saturate as this will affect the dry time.

Coverage

Coverage depends on fabric type. 1 gallon will provide coverage for approximately 200 square feet.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600 Fax: 248-587-5606 | www.gccdatasheets.com