



TYPICAL PROPERTIES

- Appearance: White liquid with a slight acrylic odor
- pH: 6-8

CarpetGeneral Carpet Stain Guard 5818

Carpet & Upholstery Protector,
Stain Repellent

Description

Carpet Stain Guard 5818 is a concentrated water based carpet and upholstery protector that when applied after carpet cleaning forms an invisible shield around each fiber to resist soil and stains. Designed to replace or enhance any of the built-in stain resist properties of the carpet that may have been removed during the wet cleaning process or worn off by normal abrasion (foot traffic, vacuuming, etc.) Carpet Stain Guard 5818 provides superior repellency and outstanding soil protection for all types of residential carpet and helps carpets stay cleaner, brighter, newer and fresher through all kinds of daily wear! It may also be applied to water safe upholstery and drapery fabrics.

Recommended Application

1

Always pretest an area to be cleaned to insure compatibility with the cleaner.

2

Dilute Carpet Stain Guard Concentrate 5818 1 to 4-5 parts water.

3

Apply diluted solution with a spray bottle.

Spray a fine mist and thoroughly cover the surface.

4

Let applied area dry for a minimum of one hour

for maximum protection against spills, soils, and stains.

Benefits

- Concentrated to save on shipping costs.
- Helps protect against both oil- and water-based stains.
- Superior repellency to clean up spills before they sink in
- Ideal for carpet, rugs, stairways, hallway and stairway runners, bath mats, drapery, and more

Material Compatibility

In general, Carpet Stain Guard 5818 can be used on cotton, polyester, silk, wool, acrylic, nylon, and most other washable fabrics. Do not use on "X" coded fabric (fabric that cannot be cleaned with water or solvents). You can find this code on the tag sewn into your fabric item. It is always best to test on a small, out-of-the-way spot first to make sure your fabric will stay colorfast.

.....

Health & Safety

Follow safe industrial hygiene practices and wear proper protective equipment. Wash hands thoroughly after handling. Please refer to SDS for complete health and safety information.

Storage

Store material at -5 C (23 F) to 40 C (104 F). Keep away from heat, steam, sunlight, sparks and open flame.

Reapplication

Duration depends on how much traffic a surface receives. Stain Guard should be reapplied after 6 months or after every extraction cleaning.

Application

Do not over saturate fabric.

Coverage

Coverage depends on fabric type. 1 gallon of diluted solution will provide coverage for approximately 200 square feet.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com