



TYPICAL PROPERTIES

- Appearance: Thick, blue grease
- Viscosity: 10,000 – 15,000 cps
- Specific Gravity: 0.83 – 0.85
- Max. Operating Temperature: 100°F

SHIPPING

Booth Grease #2 Blue is shipped in 1 gallon metal cans, 5 gallon metal pails, or 55 gallon open head metal drums.

Booth Grease #2 Blue

Booth Grease

Description

BOOTH GREASE #2 is a thick blue petrolatum based coating that provides a protective barrier for paint booth areas that accumulate heavy amounts of paint overspray. It is ideally suited for use on center tracks, flood sheets, curtain walls, and interior of paint ventilation stacks. The protective barrier of BOOTH GREASE #2 is easily removed with scraping, as the coating remains soft and can be scraped with minimal effort.

Recommended Application

1

BOOTH GREASE #2 is used as received.

2

Apply by brush, roller or airless spray. The coating remains soft and prevents paint buildup on the surface to which it has been applied.

3

BOOTH GREASE #2 is easily removed with scraping after painting operations are completed.

Benefits

- Stable Viscosity
- Easy to use
- Stays soft
- Easily removed
- No SARA or HAP reportables

Health & Safety

Please refer to SDS for complete health and safety information.

Removal

The protective barrier is easily removed with scraping, as the coating remains soft and can be scraped with minimal effort.

12336 Emerson Dr. | Brighton, MI 48116 | 248-587-5600
Fax: 248-587-5606 | www.gccdatasheets.com