

Studio Protectfilm 5140



TYPICAL PROPERTIES

- Color: clear
- Weight: 8.87 lbs/gallon
- Viscosity: 50-60 sec on Zahn 4 cup
- Flashpoint: None

SHIPPING

Studio Protectfilm 5140 is shipped in 1 gallon metal cans, 5 gallon plastic buckets, or 55 gallon open head plastic drums.

Peelable Coating

Description

Temporary decoration of a studio floors and peelable paint for makeover on vehicles, equipment and buildings used in filming. This strippable coating for Studio Floors and Cyclorama Walls allows fast turnaround for different decorative effects with minimum amount of downtime. The film and TV industries have found the coatings invaluable for recreating scenes or providing temporary color to vehicles and blanking out unwanted signage. Allows cost effective temporary advertising on large structures, buildings, including walkways, floors, roofs and vehicles. It can be used on aircraft, motor vehicles and trains and can transform large structural areas into an advertising canvass for an event or product launch.

Recommended Application

1

Studio Protectfilm is normally used as received.
It is applied by airless spray, roller or brush.

2

Studio Protectfilm is applied to form a film thickness in the range of 2 to 5 mils (.002" to .005").

3

The sprayed peelable coating air-dries in 10 minutes to 3 hours, depending on thickness of the coating, humidity, temperature and air movement.
Application temperature is ambient to no lower than 60° F. Humidity will effect dry times.

Benefits

- Multifunctional product.
- Effective protection.
- Efficient delivery systems that make it economical to treat hard-to-protect items.
- Easy application.
- Improved health, safety, and pollution control.
- Elimination of extra processing steps in most cases