



TYPICAL PROPERTIES

- Appearance: Clear liquid
- Odor: Vanilla odor
- pH: N/A; product is solvent based
- Flash Point: 102°F (minimum)
- Vapor Pressure: 4.5
- Specific Gravity: 0.87-0.88
- VOC: 7.2-7.4 lbs/gallon

Paint Booth Stripper 55

Solvent Based Paint Remover

Description

Paint Booth Stripper 55 is a low odor blended solvent for removal of paints and other soils from the floor in the spray booth area of an automotive assembly plant. It is usually applied by hand using a sponge, cloth or mop. The chemical composition of this formulation has been selected to provide effective paint removal while minimizing employee and environmental dangers.

Recommended Application

- 1 PBS - 55 is used as received.
- 2 PBS-55 can be applied by brush, mop, or sponge.
A uniform application will insure more consistent performance.
- 3 PBS 55 will evaporate at room temperature.
No additional cleaning is necessary.

Benefits

- Low odor
- Does not contain chlorinated solvent
- Does not contain Naphthalene
- Quick evaporation

Health & Safety

The cleaning solution contains petroleum solvents. Do not get in eyes, on skin or on clothing. Please refer to SDS for complete health and safety information.

Surfaces

Aluminum, Composite Materials, Stainless Steel, Ferrous, Non-Ferrous

Application

Time: 5-30 minutes.
Temperature: Ambient